



EVALIGRASS[™]

www.evaligrass.com

APPLICATION AREAS

Garden walls, sports fields surroundings, road sides and corners, wall covering, roofs and vertical landscaping areas.

SYSTEM DESCRIPTION

Evaligrass has a perfect design and natural view and it helps you to cover anywhere fastly in a simple way.

FEATURES

Installation of Evaligrass is very easy. It is wire fence which is galvanized, PVC coated, specially formulated artificial grass which has resistance to UV. It keeps its fresh look all seasons.

EVALIGRASS[™]

TECHNICAL INFORMATION

Measurements	Height: 100 cm, 120 cm, 150 cm, 200 cm	Roll Length: 10 m	Roll Widht: 40 cm
Weight	2.500 gr/ m ²		
Galvanized wire	1,60x2 : 3,20 mm hot dipped galvanized double twisted		
Artificial grass	UV reinforced PVC grass		

INSTALLATION METHOD

Roll Wallgrass	Evaligrass which is manufactured in rolls secured from the corners before assembly is done and after that fixed with special Evaligrass connection wires at intervals of 50 cm.
Panel Wallgrass	Evaligrass products which are produced as panels secured with special connection apparatus.

COLORS

Wallgrass	Green, Red, Yellow, Metallic Gray
Connection Apparatus	Green, Red, Yellow, Mettalic Gray

ADVANTAGES

View	Evaligrass has a natural look without any maintenance cost for years.
Maintenance free	Evaligrass does not need any maintenance to keep it clean.
Ecofriendly	It does not contain any harmful substances.You can use it at your garden or surroundings.



PRODUCT PACKAGING

Wallgrass Roll	It is packed in 100 CM-200 CM Height and 40 cm width in rolls and vertically packed in order not to give any damage to Wallgrass.
Wallgrass Panel	Can be loaded in different types without damaging Evaligrass panels.

PRODUCT STORAGE

Wallgrass Roll	Between 0 ~ +30°C
Wallgrass Panel	Between 0 ~ +30°C

PRODUCTION AND INSTALLATION PERIODS

Wallgrass Roll	Preperation of production: 3-5 Days	Production:1-7 Days	Installation:1-3 Days
Wallgrass Panel	Preperation of production: 3-5 Days	Production: 2-10 Days	Installation:1-5 Days

WARRANTY PERIODS

UV	2 Years	10 % tolerance
Fireproof	2 Years	10 % tolerance
Thread Strength	2 Years	10 % tolerance



EVALIGRASS

EXAMPLES OF APPLICATIONS



EVALIGRASSTM

www.evaligrass.com



+90 212 597 11 91 info@evaligrass.com

Head Office: Merkez Mahallesi Eski Edirne Caddesi No:1197 Arnavutköy İSTANBUL - TÜRKİYE

www.evaligrass.com